

# Manaaki (Sheet)

Myriad/Intrinsic/Avail/Kindred

SHEET PRODUCT

Construction	Tufted, Textured Loop
Sheet Size	2M width x 10M length
Yarn Type	ECONYL® Solution-Dyed Nylon Type 6
Stain Repel / Stain Resist	Standard
Dye Method	Solution Dyed
Tufted Face Weight	18 oz/yd <sup>2</sup> (610 g/m <sup>2</sup> )
Tufts*	109.7/in <sup>2</sup> (1,840/100 cm <sup>2</sup> )
Finished Pile Height	0.145" (3.7 mm)
Standard Backing	PVC-Free Maxima™ Hard Back
Recycled Content by Total Weight	18%
Nominal Total Thickness	0.27" (6.8 mm)
Nominal Total Weight	98 oz/yd <sup>2</sup> (3,323 g/m <sup>2</sup> )
Flammability (Radiant Panel Test)	CRF = 7.3kW/m <sup>2</sup> ; Smoke = 85%.mins
Indoor Acoustic Properties (NRC or αW)	≥ 0.15 (Exceeds standard acoustic requirements)
Lightfastness (AATCC 16E)	≥ 4.0 at 40 Hours
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Recommended Maintenance	MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia Pass (ISO10580:2010)
Indoor Air Quality (VOC)	Commercial Heavy Duty (CHD3* 16175)
ACCS Grading	15 year Wear Warranty
Applicable Warranties	15 year Dimensional Stability warranty 15 year Anti-Static Warranty 15 Year Castor Chair Wear Warranty
Recommended Installation Method(s)	Broadloom



Design Copyright - Milliken & Company

This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

**Ontera**  
A MILLIKEN COMPANY