

Momentum

Quantum (Plank)

MODULAR TILE - Plank

Construction	Tufted, Textured Loop
Tile Size	25 cm x 1M
Yarn Type	Milliken Certified Nylon Type 6,6
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® AF Built-In Protection†
Dye Method	Millitron®
Tufted Face Weight	20 oz/yd ² (678 g/m ²)
Tufts	103/in ² (1,595/100 cm ²)
Gauge	1/10
Stitches Per Inch	10.3
Standard Backing	PVC-Free Comfort Plus® ES Cushion
Recycled Content by Total Weight	ES Backing: 39.3% Pre-Consumer
Nominal Total Thickness	0.36" (9.1 mm)
Nominal Total Weight	104 oz/yd ² (3,526 g/m ²)
Flammability (Radiant Panel Test)	CRF = 3.2kW/m ² ; Smoke = 482%.mins
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Recommended Maintenance	MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia Commercial Extra Heavy Duty and Stairs (CEHDS)
ACCS Grading (roadrunner base)	Pass (ISO 1058:2010.)
Indoor Air Quality	Pass (ISO 1058:2010.)
Indoor Acoustic Properties (NRC or αW)	≥ 0.15 (Exceeds standard acoustic requirements)
Applicable Warranties	15 year Wear Warranty 15 year Dimensional Stability warranty 15 year Anti-Static Warranty 15 Year Castor Chair Wear Warranty
Recommended Installation Method(s)	Monolithic



Design Copyright - Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

† (EU) No 528/2012 (BPR): Contains AlphaSan® biocidal product (Zinc Pyrithione), to reduce the growth of bacteria, mold and mildew that can cause odours or staining

Ontera
A MILLIKEN COMPANY