

Patina Vibes

Patina Vibes

MODULAR TILE

Construction	Tufted, Textured Loop
Tile Size	50 cm x 50 cm
Yarn Type	Milliken Certified Wear-On® Nylon Type 6,6
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® AF Built-In Protection†
Dye Method	Millitron®
Tufts	117.6/in ² (1,821/100 cm ²)
Gauge	1/12
Stitches Per Inch	9.9
Standard Backing	PVC-Free Underscore™ ES Cushion
Recycled Content by Total Weight	ES Backing: 39.3% Pre-Consumer
Nominal Total Thickness	0.29" (7.4 mm)
Nominal Total Weight	89 oz/yd ² (3,024g/m ²)
Flammability (Radiant Panel Test)	CRF = 6.1kW/m ² ; Smoke = 262%.mins
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Recommended Maintenance	MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia Pass (ISO10580:2010.)
Indoor Air Quality	Commercial Extra Heavy Duty and Stairs (CEHDS)
ACCS Grading	Level 4 (Certificate No. 16098)
ACCS -ECS Grading	≥ 0.15 (Exceeds standard acoustic requirements)
Indoor Acoustic Properties (NRC or αW)	15 year Wear Warranty
Applicable Warranties	15 year Dimensional Stability warranty
	15 year Anti-Static Warranty
	15 Year Castor Chair Wear Warranty
Recommended Installation Method(s)	Ashlar (Brick Ashlar)



Design Copyright - Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

† (EU) No 528/2012 (BPR): Contains AlphaSan® biocidal product (Zinc Pyrithione), to reduce the growth of bacteria, mold and mildew that can cause odours or staining

Ontera
A MILLIKEN COMPANY