

Sound & Fury

Gesture Plank

MODULAR TILE - PLANK

Construction	Tufted, Textured Loop
Tile Size	50 cm x 1 m (19.7" x 39.4")
Yarn Type	ECONYL® Solution-Dyed Nylon Type 6
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® AF Built-In Protection†
Dye Method	Solution Dyed
Tufted Face Weight	17 oz/yd ² (576 g/m ²)
Gauge	1/12
Stitches Per Inch	10.2
Tufts	122/in ² (1,895/100 cm ²)
Finished Pile Height	0.14" (3.56 mm)
Standard Backing	PVC-Free Underscore™ ES Cushion
Recycled Content by Total Weight	ES Backing: 47.3% Pre-Consumer, 8.5% Post-Consumer
Nominal Total Thickness	0.31" (7.9 mm)
Nominal Total Weight	94 oz/yd ² (3,184 g/m ²)
Flammability (Radiant Panel Test)	CRF = 5.9kW/m ² ; smoke = 246%.mins
Lightfastness (AATCC 16E)	≤ 4.0 at 80 Hours
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Recommended Maintenance	MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia
Indoor Air Quality—CRI Green Label Plus™	GLP3200, Carpet Category 14X
ACCS Grading	Contract Extra Heavy Duty (CEHD)
Applicable Warranties	15 year Wear Warranty 15 year Dimensional Stability warranty 15 year Anti-Static Warranty 15 Year Castor Chair Wear Warranty
Recommended Installation Method(s)	Ashlar(Preferred); Monolithic; Quarter-turn



Design Copyright - Milliken & Company

This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

† (EU) No 528/2012 (BPR): contains AlphaSan® biocidal product (Zinc Pyrithione), to reduce the growth of bacteria, mold and mildew that can cause odours or staining.

Ontera
A MILLIKEN COMPANY