

Sound & Fury

Intensity Plank

MODULAR TILE - PLANK

| | |
|--|---|
| Construction | Tufted, Textured Loop |
| Tile Size | 50 cm x 1 m (19.7" x 39.4") |
| Yarn Type | ECONYL® Solution-Dyed Nylon Type 6 |
| Stain Repel / Stain Resist / Soil Release | StainSmart® |
| Antimicrobial | AlphaSan® AF Built-In Protection† |
| Dye Method | Solution Dyed |
| Tufted Face Weight | 17 oz/yd ² (576 g/m ²) |
| Gauge | 1/12 |
| Stitches Per Inch | 11 |
| Tufts | 132/in ² (2,044/100 cm ²) |
| Finished Pile Height | 0.13" (3.30 mm) |
| Standard Backing | PVC-Free Underscore™ ES Cushion |
| Recycled Content by Total Weight | ES Backing: 47.0% Pre-Consumer, 8.3% Post-Consumer |
| Nominal Total Thickness | 0.31" (7.9 mm) |
| Nominal Total Weight | 94 oz/yd ² (3,184 g/m ²) |
| Flammability (Radiant Panel Test) | CRF = 5.9kW/m ² ; smoke = 246%.mins |
| Lightfastness (AATCC 16E) | ≤ 4.0 at 80 Hours |
| Static Electricity (AATCC-134) 20% R.H., 70° F. | ≤ 3.5 KV |
| Recommended Maintenance | MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia |
| Indoor Air Quality—CRI Green Label Plus™ | GLP3200, Carpet Category 14X |
| ACCS Grading | Contract Extra Heavy Duty (CEHD) |
| Applicable Warranties | 15 year Wear Warranty 15 year Dimensional Stability warranty 15 year Anti-Static Warranty 15 Year Castor Chair Wear Warranty |
| Recommended Installation Method(s) | Ashlar(Preferred); Monolithic; Quarter-turn |



Design Copyright - Milliken & Company

This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

† (EU) No 528/2012 (BPR): contains AlphaSan® biocidal product (Zinc Pyrithione), to reduce the growth of bacteria, mold and mildew that can cause odours or staining.

Ontera
A MILLIKEN COMPANY