

# TEXTUS

Modular Tile

## Construction

Tufted, Textured Loop

## Tile Size

25cm x 1 m (9.8"x 39.4")

## Face Fiber

Milliken-Certified WearOn® Nylon  
Type 6,6

## Stain Repel/Stain Resist/Soil Release

StainSmart®

## Antimicrobial

AlphaSan® AF Built-In Protection

## Dye Method

Millitron®

## Gauge

1/10

## Stitches

14.4

## Tufts

144/in<sup>2</sup> (2,230/100 cm<sup>2</sup>)

## Standard Backing

PVC-Free Underscore™ ES Cushion  
Available with TractionBack®

## Recycled Content by Total Weight

ES Backing: 32% Pre-Consumer

## Nominal Total Thickness

0.31" (7.9 mm)

## Nominal Total Weight

87 oz/yd<sup>2</sup> (2,940g/m<sup>2</sup>)

## Flammability (Radiant Panel ASTM-E-648)

≤ 0.45 (Class I)  
CRF = 4.5kW/m<sup>2</sup>

## Smoke Density (NFPA-258-T or ASTM-E-662)

≤ 450

## Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)

Self-Extinguishing

## Lightfastness (AATCC 16E)

≤ 4.0 at 80 Hours

## Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

## Recommended Maintenance

MilliCare® - Refer to the Ontera  
Cleaning & Maintenance guide or  
MilliCare® Australia

## Indoor Air Quality—CRI Green Label Plus™

GLP3237, Carpet Category 5Y

## Recommended Installation Method(s)

Monolithic

## Applicable Warranties



15 year  
Wear Warranty



15 year  
Dimensional Stability warranty



15 year  
Anti-Static Warranty



15 year  
Castor Chair Wear Warranty



**Declare.**

This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



Ontera is a  
Proud Australian Manufacturer  
[www.ontera.com.au](http://www.ontera.com.au)