

Danxia (1236 Colourweave Base)

MODULAR TILE

Construction	Tufted, Textured Loop
Tile Size	50 cm x 50 cm (19.7" x 19.7")
Yarn Type	Milliken Certified Wear-On® Nylon Type 6
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® AF Built-In Protection†
Dye Method	Millitron®
Tufted Face Weight	20 oz/yd ² (678 g/m ²)
Gauge	1/8
Stitches Per Inch	8.0/in
Tufts	64 in ² (991/100cm ²)
Finished Pile Height	0.09" (2.29mm)
Standard Backing	PVC-Free Underscore® ES Cushion
Recycled Content by Total Weight	ES Backing: 26% Pre-Consumer
Nominal Total Thickness	0.31" (7.9mm)
Nominal Total Weight	96oz/yd ² (3255g/m ²)
Flammability	Radiant Panel Test. CRF = 6.0kW/m ² Smoke = 235 %.min
Lightfastness (AATCC 16E)	≤ 4.0 at 80 Hours
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Recommended Maintenance	MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia
Indoor Air Quality—CRI Green Label Plus™	GLP0793, Carpet Category 5Y
ACCS Grading	Commercial Extra Heavy Duty and Stairs (CEHDS)
ECS Grading	Level 4 (Certificate No. 16120)
Installation Methods	Monolithic; Quarter turn; Random; Brick
Applicable Warranties	15 year Wear Warranty 15 year Dimensional Stability warranty 15 year Anti-Static Warranty 15 Year Castor Chair Wear Warranty Monolithic; Quarter turn; Random; Brick



Design Copyright - Milliken & Company

† (EU) No 528/2012 (BPR): This product contains AlphaSan® biocidal product (Zinc Pyrithione), to reduce the growth of bacteria, mold and mildew that can cause odours or staining.

Ontera
A MILLIKEN COMPANY

This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

