

Nordic Stories

Isograd - Plank

MODULAR TILE - PLANK

Construction	Tufted, Textured Loop
Tile Size	25 cm x 1 m (9.85" x 39.4")
Yarn Type	Universal® Fibers Solution-Dyed Nylon Type 6,6
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlpAlphaSan® AF Built-In Protection†
Dye Method	Solution Dyed
Tufted Face Weight	16.7 oz/yd ² (566 g/m ²)
Gauge	1/12
Stitches Per Inch	10.4
Tufts	124.8/in ² (1,933/100 cm ²)
Finished Pile Height	0.13" (3.30 mm)
Standard Backing	PVC-Free Underscore™ ES Cushion
Recycled Content by Total Weight	ES Backing: 42.3% Pre-Consumer, 0.0% Post-Consumer
Nominal Total Thickness	0.30" (7.6 mm)
Nominal Total Weight	98 oz/yd ² (3,323 g/m ²)
Flammability (Radiant Panel Test)	CRF = 7.7kW/m ² ; Smoke = 222%.mins
Lightfastness (AATCC 16E)	≤ 4.0 at 80 Hours
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Recommended Maintenance	MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia
Indoor Air Quality—CRI Green Label Plus™	GLP7205, Carpet Category 13X
ACCS Grading	Commercial Extra Heavy Duty (CEHD)
Applicable Warranties	15 year Wear Warranty 15 year Dimensional Stability warranty 15 year Anti-Static Warranty 15 Year Castor Chair Wear Warranty
Recommended Installation Method(s)	Ashlar, Monolithic



Design Copyright - Milliken & Company

† (EU) No 528/2012 (BPR): Contains AlphaSan® biocidal product (Zinc Pyrithione), to reduce the growth of bacteria, mold and mildew that can cause odours or staining.

This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Ontera
A MILLIKEN COMPANY