

Quadrus

Altitude Brush

MODULAR TILE

Construction	Tufted, Cut Pile
Tile Size	50 cm x 50 cm (19.7" x 19.7")
Yarn Type	Milliken-Certified WearOn® Nylon, Multi- and Monofilament, Type 6,6 and 6
Antimicrobial	AlphaSan® AF Built-In Protection†
Dye Method	Millitron®
Tufted Face Weight	24 oz/yd ² (814 g/m ²)
Gauge	5/32
Stitches Per Inch	9.5
Tufts	60.8/in ² (942/100 cm ²)
Standard Backing	PVC-Free Comfort Plus® ES Cushion
Recycled Content by Total Weight	ES Backing: 37.5% Pre-Consumer, 0.0% Post-Consumer
Nominal Total Thickness	0.50" (12.7 mm)
Nominal Total Weight	125 oz/yd ² (4,238 g/m ²)
Flammability (Radiant Panel Test)	CRF = 6.8kW/m ² ; Smoke = 191%.mins
Lightfastness (AATCC 16E)	≤ 4.0 at 80 Hours
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Recommended Maintenance	MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia Pass (ISO10580:2010.)
Indoor Air Quality	15 year Wear Warranty
Applicable Warranties	15 year Dimensional Stability warranty 15 year Anti-Static Warranty 15 Year Castor Chair Wear Warranty
Recommended Installation Method(s)	Monolithic, Quarter-Turn



Design Copyright - Milliken & Company

This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

† (EU) No 528/2012 (BPR): Contains AlphaSan® biocidal product (Zinc Pyrithione), to reduce the growth of bacteria, mold and mildew that can cause odours or staining.

Ontera
A MILLIKEN COMPANY